

SERIES WHLG2 METAL-CASED HEATING MANTLES FOR ROUND-BOTTOM FLASKS T_{max} = 450°C

- powder coated, robust metal housing with high chemical resistance
- hand crocheted heating unit made of glass silk

Device features

- master switch
- integrated heating zone switch
 - heating zone 1 or heating zone 1+2;
- detachable plug-in connection (cable length 0.5 m)
- RCD safety plug (cable length 1.0 m)

Accessories ▶ Page 12

- rod clamp STK 2
 - for mounting set-ups



50 & 100 ml 1 heating zone
→ no heating zone switch



from 250 ml 2 heating zones



| Volumen (ml) | Flask Ø (mm) | Power (W ±10%) | Heating zones | Base opening Ø × H (mm) | Artikel-Nr. 230 VAC* | Price (€) | Delivery code |
|--------------|--------------|----------------|---------------|-------------------------|----------------------------|-----------|---------------|
| 50 | 51 | 50 | 1 | 158 × 175 | WHLG2XXX-230XX450-000050RC | 258,00 | A |
| 100 | 64 | 60 | 1 | 158 × 175 | WHLG2XXX-230XX450-000100RC | 258,00 | A |
| 250 | 85 | 120 | 2 | 158 × 175 | WHLG2XXX-230XX450-000250RC | 263,00 | A |
| 500 | 105 | 200 | 2 | 203 × 190 | WHLG2XXX-230XX450-000500RC | 296,00 | A |
| 1.000 | 131 | 300 | 2 | 203 × 190 | WHLG2XXX-230XX450-001000RC | 320,00 | A |
| 2.000 | 165 | 500 | 2 | 278 × 210 | WHLG2XXX-230XX450-002000RC | 401,00 | A |
| 3.000 | 185 | 600 | 2 | 278 × 210 | WHLG2XXX-230XX450-003000RC | 407,00 | A |

*115 V on request

SERIES WHLG2ER METAL-CASED HEATING MANTLES FOR ROUND-BOTTOM FLASKS T_{max} = 450°C

- powder coated, robust metal housing with high chemical resistance
- hand crocheted heating unit made of glass silk

Device features

- master switch
- integrated heating zone switch
 - heating zone 1 or heating zone 1+2;
- integrated power selector
 - infinitely variable power (0-100%)
- detachable plug-in connection (cable length 0.5 m)
- RCD safety plug (cable length 1.0 m)

Accessories ▶ Page 12

- rod clamp STK 2
 - for mounting set-ups



50 & 100 ml 1 heating zone
→ no heating zone switch



from 250 ml 2 heating zones



| Volumen (ml) | Flask Ø (mm) | Power (W ±10%) | Heating zones | Base opening Ø × H (mm) | Artikel-Nr. 230 VAC* | Price (€) | Delivery code |
|--------------|--------------|----------------|---------------|-------------------------|----------------------------|-----------|---------------|
| 50 | 51 | 50 | 1 | 158 × 175 | WHLG2ERX-230XX450-000050RC | 316,00 | A |
| 100 | 64 | 60 | 1 | 158 × 175 | WHLG2ERX-230XX450-000100RC | 319,00 | A |
| 250 | 85 | 120 | 2 | 158 × 175 | WHLG2ERX-230XX450-000250RC | 326,00 | A |
| 500 | 105 | 200 | 2 | 203 × 190 | WHLG2ERX-230XX450-000500RC | 357,00 | A |
| 1.000 | 131 | 300 | 2 | 203 × 190 | WHLG2ERX-230XX450-001000RC | 378,00 | A |
| 2.000 | 165 | 500 | 2 | 278 × 210 | WHLG2ERX-230XX450-002000RC | 454,00 | A |
| 3.000 | 185 | 600 | 2 | 278 × 210 | WHLG2ERX-230XX450-003000RC | 471,00 | A |

*115 V on request