

SERIES WHLMG3ER METAL-CASED HEATING MANTLES FOR ROUND-BOTTOM FLASKS
T_{max} = 450°C

- powder coated, robust metal housing with high chemical resistance
- hand crocheted heating unit made of glass silk
- Variable-volume, metal-cased heating mantle for different flask sizes (see ordering data)

Device features

- master switch
- integrated heating zone switch
 - heating zone 1 or heating zone 1+2 or heating zone 1+2+3;
- integrated power selector
 - infinitely variable power (0-100%)
- detachable plug-in connection (cable length 0.5 m)
- RCD safety plug (cable length 1.0 m)

Accessories ▶ Page 12

- rod clamp STK 2
 - for mounting set-ups



3 heating zones



| Volumen (ml) | Flask Ø (mm) | Power (W ±10%) | Heating zones | Base opening Ø × H (mm) | Artikel-Nr. 230 VAC* | Price (€) | Delivery code |
|--------------|--------------|----------------|---------------|-------------------------|----------------------------|-----------|---------------|
| 50-250 | 51-85 | 150 | 3 | 158 × 175 | WHLMG3ER-230XX450-000250RC | 356,00 | A |
| 250-1.000 | 85-131 | 360 | 3 | 203 × 190 | WHLMG3ER-230XX450-001000RC | 401,00 | A |
| 1.000-3.000 | 131-185 | 600 | 3 | 278 × 210 | WHLMG3ER-230XX450-003000RC | 479,00 | A |

*115 V on request

SERIES WHLSG2ER METAL-CASED HEATING MANTLES FOR ROUND-BOTTOM FLASKS
T_{max} = 450°C

- powder coated, robust metal housing with high chemical resistance
- Corrosion-resistant heating shell with optimal thermal conductivity
- Ideally suited for baths or catching leaking fluid due to vessel breakage

Device features

- master switch
- integrated heating zone switch
 - heating zone 1 or heating zone 1+2;
- integrated power selector
 - infinitely variable power (0-100%)
- detachable plug-in connection (cable length 0.5 m)
- RCD safety plug (cable length 1.0 m)

Accessories ▶ Page 12

- rod clamp STK 2
 - for mounting set-ups



2 heating zones



| Volumen (ml) | Flask Ø (mm) | Power (W ±10%) | Heating zones | Base opening Ø × H (mm) | Artikel-Nr. 230 VAC* | Price (€) | Delivery code |
|--------------|--------------|----------------|---------------|-------------------------|----------------------------|-----------|---------------|
| 250 | 85 | 120 | 2 | 158 × 175 | WHLSG2ER-230XX450-000250RC | 437,00 | A |
| 500 | 105 | 200 | 2 | 203 × 190 | WHLSG2ER-230XX450-000500RC | 477,00 | A |
| 1.000 | 131 | 300 | 2 | 203 × 190 | WHLSG2ER-230XX450-001000RC | 481,00 | A |
| 2.000 | 165 | 500 | 2 | 278 × 210 | WHLSG2ER-230XX450-002000RC | 522,00 | A |

*115 V on request